



Labeling Solutions

Top and Bottom Labeling Machine

Configurable to accommodate diverse application requirements, these machines offer flexibility through their ability to be fitted with conveyor belts of various dimensions.

- Built on the innovative QKE technology kit, this top and bottom labeling system boasts a modular design that ensures rapid deployment and versatility. Its reliability is unmatched, tackling even the most daunting labeling tasks with ease.
- Whether product surfaces are smooth and flat or irregular and recessed, the machine consistently delivers high-throughput performance, making it an ideal solution for a wide range of applications.



Useful options

- For added convenience, we offer flexible placement options with our machines, which can be designed to be mobile, allowing you to position them precisely where they're most needed.
- Variable data printing capabilities can be seamlessly added to a hot-foil printer's functionality.
- With adaptable conveyor belt sizes, these machines can cater to diverse needs, making them a versatile solution for numerous industries and uses.

Flexible installation locations

- Wherever the need arises, our models can be easily relocated, thanks to their availability in mobile formats, providing you with the flexibility to place the machine exactly where it's needed now.

Always come out on top

- Built on QKE's modular technology, these machines boast a consistent and reliable performance, making them ideal for labeling applications that require flexibility.
- With their compact design, they can be easily configured for top or bottom labeling and are readily available on short notice.

The foundation for your success

- The machine can be quickly and easily reconfigured for seamless label reel changeovers to accommodate varying insertion and working positions. Additionally, the integrated conveyor belt streamlines the labeling process, eliminating the need to rotate products during application.

Top and Bottom Labeling Machine

Labeling type

Top labeling
Bottom labeling
Side Labeling
Top & bottom labeling

Product specifications

Rectangular, dimensionally stable

Product dimensions

Top labeling: 30 - 300 x 50 - 250 x 50 - 150 mm (L x W x H)
Bottom labeling: 140 - 300 x 50 - 250 x 50 - 200 mm (L x W x H)
Top & bottom labeling: 140 - 300 x 50 - 250 x 50 - 150 mm (L x W x H)

Label dimensions

Top labeling: 15 - 160 x 30 - 300 mm (W x L)
Bottom labeling: 15 - 120 x 30 - 300 mm (W x L)

Capacity

Up to 250 products/minute

Power supply

220 V, 50 Hz, 1/3 Phase

Compressed air supply

6 bars (optional)

Printer

Various hot-foil printers (optional)

Components

Conveyor belt, side guide for products, applicator(s), control panel
Capacity: Up to 330mm spool diameter

Options

Transfer plates at infeed and outfeed, moveable version,
digital position indicators



New quote: +84 (0)838.03.06.09

Call **+84-838-03-06-09**

Email **sales@qke.vn**

or visit **www.qke.vn/en/**

QKE© Global

4th Floor Dong Nam Building, 322 Tay Thanh, Tay Thanh Ward,
Tan Phu District, Ho Chi Minh City, Vietnam

©2023 QKE Global — All rights reserved.

QKE Global's policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice.

